

POLY STUDIO



SPECIFICATIONS

DIMENSIONS

- Unit dimensions:
 - 105 mm x 700 mm x 70 mm = 4.2" x 27.3" x 2.8" (HxWxD) without stand
 - 156 mm x 700 mm x 70 mm = 6.2" x 27.3" x 2.8" (HxWxD) with stand
- Weight:
 - 5 lbs 2.6 oz (2342 g) without stand
 - 6 lbs 4.7 oz (2856 g) with stand
- Remote control dimensions:
 - 183 mm x 40 mm x 19 mm = 7.2" x 1.6" x .75" (HxWxD)

APPLICATION REQUIREMENTS

- Supported operating systems
 - Windows 7, 8.1, 10
 - MacOS 10.12, 10.13, 10.14
- Support for standard audio and video device drivers
 - UAC 1.0 Audio
 - UVC 1.1/1.5 Video
 - HID 1.11

POWER REQUIREMENTS

- 12VDC/5A @ 100~240VAC, 50/60 Hz

PACKAGE INCLUDES

- Poly Studio
- Remote control with 2 AAA batteries
- Power adapter
- 5 m USB 2.0 cable (Type-C to Type-A)
- Wall mount kit
- Setup sheet

OPTIONAL ACCESSORIES

- Expansion microphone
- Display mount

DATA SHEET_POLY STUDIO

CAMERA

- 120-degree FOV
- UHD 2160p (4K) capture resolution
- Automatic people framing & speaker tracking
- 5x zoom / EPTZ
- 2 camera presets

AUDIO

- Poly Acoustic Clarity technology provides full-duplex conversations, acoustic echo cancellation and background noise suppression
- Poly NoiseBlock technology
- Poly Acoustic Fence technology
- Mute/unmute controls
- Stereo microphones:
 - 6-element beamforming microphone array
 - 12 ft pickup range
 - 120 Hz-16 kHz frequency response
- Stereo speakers:
 - 100 Hz-20 KHz frequency response
 - Output = 90 dB @ 0.5m

INTERFACES

- 1x USB 3.0 Type-C port (with 2.0 compatibility)
- Power connector
- Optional external microphone
- 3.5 mm stereo Audio In
- Kensington security lock
- 802.11ac Wi-Fi wireless networking for manageability; IEEE 802.11a/b/g/n compatible
- Bluetooth® 4.2

LEARN MORE

For more information on Poly Studio, visit poly.com/studio

APPLICATION COMPATIBILITY

- Compatible with any application that supports standard USB audio and video drivers, including but not limited to:
 - Certified for Microsoft Teams and Skype for Business
 - Zoom Certified
 - LogMeIn GoToMeeting®
 - BlueJeans Network
 - Google Hangouts™ communication platform
 - Amazon Chime
 - Cisco Webex®
 - VidyoDesktop™
 - Polycom RealPresence Desktop

SECURITY

- 802.1x support
- Certification management

MANAGEABILITY (VIA WI-FI)

- Polycom Companion App (running on Win/Mac PC connected to device)
- Polycom RealPresence Resource Manager
- Polycom Device Management Service

WARRANTY INFORMATION

- 1-year limited hardware warranty

COUNTRY OF ORIGIN

- Laos

ENVIRONMENTAL

- Operating temperature: 32-104°F (0-40°C)
- Relative humidity: 5-95%, noncondensing
- Storage temperature: -13-160°F (-25°-70°C)